

City of Elysian

Water & Sewer Permit Application

JOB SITE ADDRESS _____

PROPERTY OWNER

Name/Company _____ Phone _____

Address _____

City _____ State _____ Phone _____

CONTRACTOR

Company _____ Phone _____

Address _____

City _____ State _____ Phone _____

Contact Name _____ Phone _____

Email _____

MN State Master Plumber's License # _____ OR Pipe Layer Certification Card # _____

WORK TO BE DONE

Permit Type: _____ Sewer & Water _____ Sewer Only _____ Water Only

Work Type: _____ New Construction _____ Repair _____ Replace

Water: Pipe Size _____ Pipe Length _____ Pipe Material _____

Sewer: Pipe Size _____ Pipe Length _____ Pipe Material _____

Work Impact (Yes/No): Street _____ Sidewalk _____ Curb _____

The undersigned acknowledges that this application has been read and that the above information is correct and agrees to comply with all ordinances, laws, and applicable codes of the City of Elysian, County of Le Sueur, and the State of MN. This Permit becomes void if work does not begin within 180 days or is suspended at any time for over 180 days.

Applicant Signature _____ Date _____

OFFICE USE ONLY

Water &/or Sewer Permit (\$50.00) \$ _____

Sewer Availability Charge-SAC (\$1,600) \$ _____

Water Availability Charge-WAC (\$1,500) \$ _____

Water Meter(s) (\$240 for up to a 1" meter, additional sizes available for cost) \$ _____

Total \$ _____

Date _____ Receipt # _____ Permit # _____ Issued by _____

Required Inspections by Public Works Department: _____ Rough-In (Air Test) _____ Visual _____ Other

REQUIREMENTS FOR INSTALLATION OF SEWER & WATER FROM CURB STOP TO HOUSE

WATER:

1. No curb stops in the driveway. If a curb stop must be placed in the driveway, contact the Public Works Department at 763-263-2268 before starting work.
2. The curb stop must have concrete block placed under it.
3. Water line must be a minimum of one inch (1") Type K copper.
4. Water lines must be insulated if less than eight feet (8') deep with two inch (2") thick by four foot (4') wide high-density Styrofoam; water lines less than six feet (6') deep must be insulated with three inch (3") thick by eight foot (8') wide density Styrofoam.
5. Water lines placed under driveways must be insulated with two-inch (2") thickness by four foot (4') wide high-density Styrofoam.
6. The water must have an inside valve with a flared connection.
7. No couplings allowed unless approved by the City of Elysian including the area from the curb stop to the first valve in the structure.
8. Water line must be flushed after installation.
9. After inspection by the City, water must be shut off at the curb stop.
10. All curb boxes must have a rod installed
11. Curb box top must be level with surface.
12. If water line is installed during the winter and can't be tested by turning on the water, air testing must be done at the time of the initial inspection; minimum eighty (80) psi.

SEWER:

1. Sewer line must be schedule 40PVC (ASTMD1785) or SDR26 PVC ASTM SPEC D3034 and a minimum of four inch (4") in diameter.
2. Sewer must have a clean out within two feet (2') of the outside wall and every seventy-five feet (75') thereafter. Clean out must have a minimum metal one foot (1') stake installed next to it. At no time, may the outside clean out be located under a structure/deck unless it is a minimum forty-eight inches (48") above grade.
3. A twelve (12) gauge copper wire must be run on top of the sewer for locating purposes.
4. Sewer line must have a minimum one-eighth inch (1/8") per foot slope.
5. Sewer line must be pressure tested, 5 psi minimum.

GENERAL REQUIREMENTS:

1. Contractor shall obtain a sewer/water dig-in permit at City Hall prior to starting work; the contractor will be notified of the permit fee.
2. Contractor shall provide the City of Elysian with a general liability certificate of insurance in the amount of \$100,000.00 minimum.
3. Contractor must have work inspected by the Public Works Department. Curb stop/box must be inspected and approved by the Public Works Department prior to Building Final. Please schedule inspections through the City Hall by calling 507-267-4708.
4. All trenches must meet OSHA standards.
5. The City shall charge the contractor for labor and material if improperly installed.
6. Anyone conducting plumbing activities, such as connecting a building to a septic tank, sewer main, or water source, must provide evidence of a \$25,000.00 code compliance bond and must also provide evidence of having a pipe layer certification card or plumber's license.